



WB-2 Rod Kit



Available Diameters	Max System Tensile Force (FOS 1.95)		System Lengths	
1 1/8"	14,869 lb	66,141 N	20 ft, 24 ft, 30 ft	6.1 m, 7.3 m, 9.1 m
1 1/4"	18,883 lb	83,996 N	20 ft, 24 ft, 30 ft	6.1 m, 7.3 m, 9.1 m
1 1/2"	27,379 lb	121,788 N	20 ft, 24 ft, 30 ft	6.1 m, 7.3 m, 9.1 m
1 3/4"	37,026 lb	164,700 N	24 ft, 28 ft, 32 ft	7.3 m, 8.5 m, 9.8 m
2"	48,718 lb	216,708 N	24 ft, 28 ft, 32 ft	7.3 m, 8.5 m, 9.8 m



Material	6061-T6 Marine Grade Aluminum
Standard Packaging	Anchor Rod, Stub Rod, Turnbuckle, Wale Nut, Aluminum Nut
Compatibility	WB-2 Wale

Physical properties are defined by ASTM testing standards, The Aluminum Association Design Manual, The Naval Facilities Design Manual DM 7.2, The US Army Corps of Engineers General Design Guide: PVC Sheet Pile and/or standard engineering practice. The values shown are nominal and may vary. The information found in this document is believed to be true and accurate. No warranties of any kind are made as to the suitability of any CMI product for particular applications or the results obtained there from. Crane Materials International is a Crane Building Products® company. ShoreGuard®, The ShoreGuard Seawall System™, C-Loc®, TimberGuard®, GeoGuard®, Dura Dock®, Shore-All®, GatorGates®, GatorDock Elite™, ArmorWare™, ArmorRod™, Box Profile™, UltraComposite™, Elite Wall™, Elite Panel™, Elite Fascia Panel™, Flat Panel™, XCR™, XCR Technology™, XCR Vinyl™, GatorBridge™, Gator Aluminum™, Gator Sheet Piling™, GatorDock™, I-Beam Lock™, Textured Slate™, Crane Materials International™ logo, CMI Sheet Piling Solutions™, Aqua Terra System™, Endurance™, Endurance CSPTM, Polaris™, Eclipse™, GridSpine™, 21 Poly™, PileClaw™, SheerScape™, SheerScape Retaining Wall Systems™, Sheer Panel™ and CMI Waterfront Solutions™ are trademarks, service marks or trade names of Crane Materials International. United States and International Patent numbers 4,674,921; 4,690,588; 5,292,208; 5,145,287; 6,000,883; 6,033,155; 6,053,666; D420,154; 6,575,667; 7,059,807; 7,056,066; 7,025,539; 7,393,482; 5,503,503; 5,803,672; 6,231,271; 1,245,061 CA and other patents pending. © 2011 Crane Materials International. All Rights Reserved.